## **R59003059** SOCKET SET 3/8"

## 59 pieces

- > Coupler based on DIN 3120 A 10, ISO 1174, with ball lock
- > Square drive as per DIN 3120 C 10, ISO 1174, with ball retention groove
- > 2C reversible ratchet 3/8": lever for reversing clockwise/anticlockwise direction, push-button release, fine-toothed, oval head, dual-material handle for ease in gripping, for sockets
- > Socket 3/8": bi-hex, metric, short, as per DIN 3124, ISO 2725
- > Socket 3/8": hex, metric, long, as per DIN 3124, ISO 2725
- > Spark plug socket 3/8" with pressed-in holding rubber and extra drive hex Size 19
- > Spark plug socket 3/8" with pressed-in holding rubber and extra drive hex Size 22
- > Screwdriver bit socket 3/8": for hex screws, with pressed-in, phosphated pin
- > Screwdriver bit socket 3/8": slotted, with pressed-in, phosphated pin
- > Screwdriver bit socket 3/8" PH: with pressed-in, phosphated pin
- > Screwdriver bit socket 3/8" PZ: with pressed-in, phosphated pin
- > Screwdriver bit socket 3/8" TX: with pressed-in, phosphated pin
- > Socket extension 3/8"
- > Convertor/slider 3/8" x 1/2": for driving sockets and screwdriver bit sockets
- > Universal joint 3/8": screwed-on joint , acc. to DIN 3123 C 10
- > Reducer 3/8" to 1/4"

Code

> Chrome-vanadium steel, matt satin chrome-plated

No.

> For hand-operated screw work

- > Plastic case in GEDORE red Design
- > Clamp-secured tools
- > Metal hinges/fastener





pieces

⊖ kg ⊖

3300054	R59003059	3/8" 2C lever reversible ratchet, fine-toothed,	383	272	80	59	4.8
		72 teeth   180 mm					
		3/8" socket hexagon bi-hex 6 7 8 9 10 11 12 13 14					
		15 16 17 18 19 20 21 22 24 mm					
		3/8" socket hexagon hex long 8 9 10 11 12 13 14 15					
		17 19   L.63mm					
		3/8" spark plug socket 16 21 mm   65 mm					
		3/8" screwdriver bit socket in-hex 3 4 5 6 7 8 10 48 m	ım				
		3/8"screwdriver bit socket slotted 5.5 7 8 48 mm					
		3/8" screwdriver bit socket cross-head PH 1 2   48 mm					
		3/8" screwdriver bit socket cross-head PZ 1 2 48 mm					

Т

W

D

3/8" screwdriver bit socket TX T25 T27 T30 T40 T45

T50 T55 | 48 mm

3/8" socket extension 75 250 mm

3/8" universal joint | 49 mm Reducer 3/8" - 1/4" | 27 mm

Contents

Socket extension piece/slider 3/8" x 1/2" | 44 mm