

4549

TORQUE WRENCH TORCOFIX K

1-50Nm / 0.75-37lbf·ft

Use:

- › For use in almost all industrial manufacturing areas.
- › For controlled nut and bolt tightening.

Features:

- › Adjustable torque wrench with a square drive and integrated ratchet head function.
- › For controlled bi-directional tightening.
- › Interchangeable mushroom head square drive with ball-locking mechanism as per DIN 3120.
- › In accordance with DIN EN ISO 6789, traceable to national norms.
- › Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- › Lever breaking mechanism with a castor guarantee tactile impulse and audible actuation signals.
- › Double scale Nm and lbf.ft behind window with magnifying effect.
- › Black plastic handgrip with slip-resistant ribbed surface.
- › Full-metal construction from high strength aluminium alloy.
- › Additional micrometer scale with a Nm graduation of 0.1, 0.25, 0.5 or 1Nm.
- › Supplied with a calibration certificate.
- › Unique serial number for traceability.

1/4"

3/8"



Code	No.	■"	■	Nm	lbf·in	↳ mm ◀	⚖ kg
2201429	4549-00	1/4	6.3	1-5	0,75-3,7	225	0.323
1545132	4549-02	1/4	6.3	2-25	1,5-18	285	0.450
1545140	4549-05	3/8	10.0	10-50	7,5-37	335	0.540