

4550

TORQUE WRENCH TORCOFIX K

40-750Nm / 30-550lbf·ft

1/2"

3/4"

Use:

- > For use in almost all industrial manufacturing areas.
- > For controlled nut and bolt tightening.

Features:

- > Adjustable torque wrench with a square drive and integrated ratchet head function.
- > For controlled bi-directional tightening.
- > Interchangeable mushroom head square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Lever breaking mechanism with a castor guarantee tactile impulse and audible actuation signals.
- > Double scale Nm and lbf.ft behind window with magnifying effect.
- > Black plastic handgrip with slip-resistant ribbed surface.
- > Sturdy, varnished tubular steel construction, with zinc plated ratchet head and top grade plastic parts.
- > Additional micrometer scale with a Nm graduation of 0.1, 0.25, 0.5 or 1Nm.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



| Code | No. | ■" | ■ | Nm | lbf·ft | ◀ mm ▶ | ⚖ kg |
|----------------|---------|-----|------|---------|---------|--------|------|
| 7601610 | 4550-20 | 1/2 | 12.5 | 40-200 | 30-150 | 485 | 1.10 |
| 7674330 | 4550-40 | 3/4 | 20.0 | 80-400 | 60-300 | 665 | 1.86 |
| 7674760 | 4550-55 | 3/4 | 20.0 | 110-550 | 80-405 | 960 | 3.56 |
| 1521365 | 4550-75 | 3/4 | 20.0 | 150-750 | 110-550 | 1240 | 4.50 |