

# DMK

## TORQUE WRENCH DREMASTER®

1/2" 3/4"



### 20-850Nm / 15-630lbf·ft

#### Use:

- > For use in all areas of industrial manufacturing.
- > For controlled nut and bolt tightening.

#### Features:

- > Adjustable torque wrench with a square drive and integrated ratchet head function.
- > For controlled bi-directional tightening.
- > Interchangeable mushroom head square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Lever breaking mechanism with a castor guarantee tactile impulse and audible actuation signals.

- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Sturdy, satin-chrome plated tubular steel construction, with chrome plated ratchet head and top grade plastic parts.
- > Ergonomically shaped, two-component plastic grip with calibration aid.
- > Double scale Nm and lbf.ft behind window with magnifying effect.
- > Additional micrometer scale with a Nm graduation of 0.1, 0.25, 0.5 or 1Nm.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



Code	No.	1/2"	3/4"	Nm	lbf·ft	Scale ring	Scale ring	mm	kg
2641232	DMK 100	1/2	12.5	20-100	15-75	5 N-m	0,5 N-m	423.5	1.10
2641240	DMK 200	1/2	12.5	40-200	30-150	10 N-m	1 N-m	514.5	1.30
2641259	DMK 300	1/2	12.5	60-300	45-220	10 N-m	1 N-m	606.4	1.50
2641267	DMK 400	3/4	20.0	80-400	60-300	10 N-m	1 N-m	714.8	2.40
2641275	DMK 550	3/4	20.0	110-550	80-405	10 N-m	1 N-m	953.2	3.80
2641283	DMK 750	3/4	20.0	150-750	110-550	10 N-m	1 N-m	1,228.2	4.90
2641291	DMK 850	3/4	20.0	250-850	185-630	10 N-m	1 N-m	1,375.2	5.20